




Binnenunit	Type	<b>ASD07RIX</b>		Type	Unité intérieure
	Fabriekscode	ASHG07KGTE		Code de fabrication	
Koelmiddel		R32			Réfrigérant
Verwarming (*)	Vermogen	kW	2,8	kW	Puissance
					Chauffage (*)
Koeling (*)	Vermogen	kW	2,5	kW	Puissance
					Refroid. (*)
Binnendeel	Debiet Q/L/M/H	m <sup>3</sup> /h	270/430/540/650	m <sup>3</sup> /h	Débit Q/L/M/H
	Geluidsdruk Q/L/M/H (1m)	dB(A)	21/29/33/38	dB(A)	Niv. son. press. Q/L/M/H (1m)
	Werkingslim. verwarmen	°C	16~30	°C	Plage de fonct. chauff.
	Werkingslim. koelen	°C	18~32	°C	Plage de fonct. refroid.
	Hoogte-breedte-lengte	mm	270-834-215	mm	Hauteur/largeur/profond.
	Gewicht	kg	10	kg	Poids
Tech.install.	Expansie		Ext.		Détente
	Koelleidingen	inch	3/8 -1/4	inch	Lignes frigorifique
	Sectie tssn bi en bu	mm <sup>2</sup>	4G1.5	mm <sup>2</sup>	Section entre int. et ext.
	Diam. condensafvoer	mm	11,8/15-16,7	mm	Diam. évac. Condensat

(\*) gegevens volgens de norm EN14511

(\*) SCOP &amp; SEER based on (EU)626/2011

(\*) suivant la norme EN14511

