




Binnenunit	Type	<b>AS24RIX</b>		Type	Unité intérieure
	Fabriekscode	ASHG24KMTE		Code de fabrication	
Koelmiddel		R32			Réfrigérant
Verwarming (*)	Vermogen	kW	8	kW	Puissance
					Chauffage (*)
Koeling (*)	Vermogen	kW	7,1	kW	Puissance
					Refroid. (*)
Binnendeel	Debiet Q/L/M/H	m <sup>3</sup> /h	510/640/850/1170	m <sup>3</sup> /h	Débit Q/L/M/H
	Geluidsdruk Q/L/M/H (1m)	dB(A)	29/35/40/49	dB(A)	Niv. son. press. Q/L/M/H (1m)
	Werkingslim. verwarmen	°C	16~30	°C	Plage de fonct. chauff.
	Werkingslim. koelen	°C	18~32	°C	Plage de fonct. refroid.
	Hoogte-breedte-lengte	mm	280-980-240	mm	Hauteur/largeur/profond.
	Gewicht	kg	13	kg	Poids
Tech.install.	Expansie		Ext.		Détente
	Koelleidingen	inch	1/2-1/4	inch	Lignes frigorifique
	Sectie tssn bi en bu	mm <sup>2</sup>	4G1.5	mm <sup>2</sup>	Section entre int. et ext.
	Diam. condensafvoer	mm	13,8/15,8-16,7	mm	Diam. évac. Condensat
(*) gegevens volgens de norm EN14511 <span style="float: right;">(*) suivant la norme EN14511</span>					

Unit: mm

